

QUICK TIE PRODUCTS, INC.

Installer Tool Requirements

(FOR A TWO OR THREE MAN CREW)

May 25, 2006

- 1ea. – 1” Hammer Drill (SDS w/case)
- 1ea. – ½” Angle Drill (w/case)
- 1ea. – ½” Drill (w/case)
- 1ea. – air compressor
- 1ea. – Reciprocating Saw (w/case)
- 2ea. – Positive placement Nail Gun
- 2ea. – ¾” x 17” Auger Bit
- 2ea. – 5/8” x 10” Carbide Masonry Bit (SDS)
- 1ea. – ½” x 8” Carbide Masonry Bit (SDS)
- 1ea. – 5/8” Paddle Bit
- 3ea – 50’ Air Hose
- 1ea. – Blowout Nozzle
- 2ea. – 100’ 12/3 Electrical Cord
- 2ea. – 50’ 12/3 Electrical Cord
- 2ea. – 3 way Outlet Power Cord
- 2ea. – 9” Needle Nose Vice Grip
- 1ea – Dual Epoxy Gun 33oz. (Q100033HD)
- 2ea. – ½” x 6” Steel Brush (Q1000BSH)
- 2ea. – 6’ Class 1 Fiberglass Step Ladder
- 2ea. – 2’ Class 1 Fiberglass Step Ladder
- 3ea. – Protective Eye Glasses
- 2ea. – ¾” Ratchet Wrench
- 1ea. – Impact Wrench (rated at 40 to 50 foot pounds of pressure)
- 2ea. – 20oz. Carpenters Hammers
- 2ea. – 25’ Measuring Tape
- 1ea. – 1500 watt Electric Generator (optional)